

This is a full synthetic lubricant based on carefully selected very high quality base oils. This oil is extremely fuel-efficient and meets the requirements of the new Ford EcoBoost petrol engines. It ensures a reduction of fuel consumption on partial and full load operation as well as reduction of exhaust emission. It has excellent cold starting behavior giving a very good operating reliability.

Performance

- ACEA: A1 / B1 / C5
- FORD: WSS-M2C948-B
- API: SN
- JAGUAR / LAND ROVER STJR.03.5004

Features

Total engine protection : performance in keeping the engine clean.
 Fuel economy : superior fuel economy and CO2 reduction.
 Cold start : excellent fluidity at low temperature.

Applications

Meets the requirements of the Ford WSS-M2C948-B specification and is mandatory for Ford EcoBoost 1.0 3-cylinder engines and is required for further EcoBoost petrol engines. This oil can also be used where the vehicle manufacturer specifies a motor oil ACEA A1/B1 or API SN.

| Characteristics | Unit | Average |
|-------------------|--------------------|---------|
| Density at 15 °C | kg/l | 0.851 |
| Viscosity -20 °C | mPas | 5500 |
| Viscosity 40 °C | mm ₂ /s | 42.3 |
| Viscosity 100 °C | mm ₂ /s | 7.9 |
| Viscosity index | | 162 |
| Flash point COC | °C | 220 |
| Pour point | °C | -39 |
| Total Base Number | mgKOH/g | 7.6 |
| Sulphated Ash | % | 0.8 |