

This is a full synthetic lubricant based on carefully selected very highly refined base oils for automatic transmissions , meeting the requirements of most American, Japanese and European manufacturers.

Performance

- AISIN-WARNER: JWS 3309
- AISIN-WARNER: JWS 3314
- AISIN-WARNER: JWS 3317
- ALLISON : TES 295
- BMW: ETL 7045E
- BMW: ETL 8072B
- BMW: LA 2634
- BMW: LT 71141
- CHRYSLER: ATF +3 AND +4
- FIAT: 9.55550-AV4
- FORD: MERCON V
- FORD: WSS-M2C922-A1
- GM: DEXRON III-H, III G & IID
- HONDA: ATF Z-1
- HYUNDAI: SP-III
- MB: 236.10
- MB: 236.11
- MB: 236.3
- MB: 236.5
- MB: 236.7
- NISSAN: MATIC-K
- NISSAN: MATIC-W
- PSA: P/N Z 000169756
- TOYOTA: TYPE T-IV
- VW: G 052 055
- VW: G 052 162
- VW: G 052 533
- VW: G 052 990
- VW: G 055 025

Features

Frictional properties : very smooth gear shifting, no vibration.
 Anti-wear protection : significantly extended transmission life.
 Extended oil life : excellent thermal and oxidation stability.

Applications

Its versatile nature guarantees it can be used in automatic transmissions and torque convertors for most passenger cars, off-road vehicles and SUVs.

Characteristics	Unit	Average
Density at 15 °C	kg/l	0.849
Viscosity -40 °C	mPas	12000
Viscosity 40 °C	mm _t /s	32.7
Viscosity 100 °C	mm _t /s	7.02

Viscosity index		184
Flash point COC	°C	218
Pour point	°C	-48
Color		RED
