Cars

Trans ATF ZF 8

This is a full synthetic lubricant based on carefully selected very high quality base oils that has been specifically developed for ZF 6, 8 and 9-speed automatic transmissions. Its particular formulation ensures a trouble-free operation and smooth gear shifting.

Performance

- ZF 8 HP
- ACURA ATF TYPE 3.0
- BMW: 83222152426
- BMW: 83222305397
- FIAT: 9.55550-AV5
- HONDA ATF TYPE 3.1
- LAND ROVER: LR023288
- MOPAR: 68157995AB
- VW G 055 162
- ZF S671 090 312
- ACURA 08200-9016a
- ATF L 12108
- BMW: 83225A12A00
- CHRYSLER: 68157995AA
- HONDA 8200-9017
- JAGUAR: 02JDE26444
- LAND ROVER: LR023289
- MOPAR: 68218925AA
- VW 060 162
- ZF TE-ML 11

Features

Exclusively intended for the ZF 6,8 and 9 speed automatic transmissions, as fitted in VW, BMW, Jaguar, Land Rover, Jeep, Chrysler and FIAT group.

Characteristics	Unit	Average
Density at 15 °C	kg/l	0.845
Viscosity -40 °C	mPas	9500
Viscosity 40 °C	mm¸/s	28.1
Viscosity 100 °C	mm¸/s	5.94
Viscosity index		164
Flash point COC	°C	210
COLOR		GREEN